

# ICIP-B3000 AF-I

## 3 Megapixel Indoor/Outdoor, Full-Size Bullet IR IP Camera

---



A weatherproof, day/night, smart 3 Megapixel bullet camera – the ICIPB3000AF-I. This sleek bullet design contains a high resolution, 3 Megapixel Aptina CMOS sensor, capable of outputting a crisp, clear image. The optics are located behind the removable black snout, which conceals the 3 - 9mm motorized lens. This camera is IP 66 rated and highly weatherproof.

### Features

- 3 -9mm motorized
- Max. IR LEDs length 90ft
- Built-in 1/1 alarm in/out
- Micro SD memory, IP66, PoE
- Max 30fps@3.0M(2048x1536)
- Smart detection

# ICIP-B3000 AF-I

## Specifications


<b>Model</b>	ICIP-B3000 AF-I
<b>Camera</b>	
Image Sensor	1/3" 3Megapixel Aptina CMOS
Effective Pixels	2048(H)×1536(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/4~1/10000s
Min. Illumination	0.01 ux/F1.4(Color), 0Lux/F1.4(IR on)
S/N Ratio	More than 50dB
Video Output	1 port
<b>Camera Features</b>	
Max IR LEDs Length	90Ft
Day/Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
<b>Lens</b>	
Focal Length	3~9mm motorized
Max Aperture	F1.4
Focus Control	Auto
Angle of View	H: 86.5°~28.6°
Lens Type	Motorized/ Auto Iris(DC)
Mount Type	Board-in Type
<b>Video</b>	
Compression	H.264 / MJPEG
Resolution	3M(2048×1536)/1080P(1920×1080)/720P(1280×720) /D1(704×576) /CIF(352×288)
Frame Rate	Main Stream :3M/1080P (1~25/30fps) Sub Stream1: D1/CIF(1 ~ 25/30fps) Sub Stream2: 1080P/720P/D1(1 ~ 25/30fps)
Bit Rate	H.264: 48K ~ 8192Kbps
<b>Audio</b>	
Compression	G.711a/ G.711u/ PCM
Interface	1/1 channel In/Out
<b>Smart Function</b>	
Smart Detection	Tripwire, Intrusion, Scene change, Missing/Abandoned, Audio detect, Face detect
<b>Network</b>	
Ethernet	RJ-45 (10/100/1000Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF,PSIA,CGI

Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>Auxiliary Interface</b>	
Memory Slot	Micro SD, Max 64GB
Alarm	1/1 channel In/Out
<b>General</b>	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<9W (IR on: +3W)
Working Environment	-30°C ~ 60°C/-22°F ~ 140°F, Less than 95%RH
Ingress Protection	IP66
Dimensions (WxDxH)	273.3mm x 94.8mmx 94.8mm
Weight	1.3kg

### Optional Accessories



**MNT-JUNCTION BOX 1**



**MNT-PCNRIP**



**MNT-POLIP**